



WEVER & DUCRÉ
LIGHTING

LITO 1.0

145181B4

GENERAL

Wall
Recessed
Jet Black
IP20
Interior
160^a to 210^b lm
9005^c

LED

3000 K

OPTICAL

Wallwasher

PHYSICAL

Length 80 mm
Width 80 mm
Height 22 mm
0.09 kg

ELECTRICAL

Total connected power 2^a to 3^b W
70^b to 80^a lm/W
PC3
0.3 m

CUTOUT




Length 70 mm
Width 70 mm
Min. ceiling thickness 12 mm
Max. ceiling thickness 18 mm
Recessed depth 35 mm

^a 350mA

^b 500mA

^c RAL Palette colors may deviate slightly due to production conditions.

Project
Type
Notes
Quantity
Date





WEVER & DUCRÉ
LIGHTING

LITO 1.0

145181B4

MOUNTING

Recessed Housing

TYPE	L · W · H (MM)	ORDERCODE
LITO	120-38-120	9 0 0 1 2 0 2 7

Plasterkit

TYPE	L · W · H (MM)	ORDERCODE
LITO	120-120-8	9 0 0 1 7 1 1 9

POWER SUPPLIES

Power Supply 350mA

TYPE	L · W · H (MM)	ORDERCODE
6W 3-22V	64-35-21	9 0 2 1 3 2 0 2

Power Supply 500mA

TYPE	L · W · H (MM)	ORDERCODE
6W 3-12V	64-35-21	9 0 2 1 4 2 0 1