



WEVER & DUCRÉ
LIGHTING

RETO 2.0

345261W5

GENERAL

Wall

Recessed

Signal White

Below IP20

Interior

490 lm

LED

3000 K

ELECTRICAL

excl. power supply

18 V

LED Inset 6 W

350 mA

Class 3

Safety distance 0.3 m

PHYSICAL

Length 200 mm

Width 30 mm

Height 80 mm

0.41 kg

CUTOUT

Length 47 mm

Width 182 mm

Min. ceiling thickness 12 mm

Recessed depth 40 mm

Project

Type


Notes

Quantity

Date



Rectangular wall recessed luminaire made from aluminium; surface Signal White; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP20; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ
LIGHTING

RETO 2.0

345261W5

MOUNTING

Concrete Housing

L · W · H (MM)

122 · 55 · 190

ORDERCODE

9 0 0 1 2 0 4 2

Recessed Housing incl. plasterkit

L · W · H (MM)

160 · 67 · 250

ORDERCODE

9 0 0 1 2 0 4 3

ELECTRICAL

Driver

TYPE

6W | 350mA | 3-22V

L · W · H (MM)

68 · 35 · 21

ORDERCODE

9 0 2 1 3 2 0 2