



WEVER & DUCRÉ
LIGHTING

RETO 0.8

345161W5

GENERAL

Wall

Recessed

Signal White

Below IP20

Interior

150 lm

LED

3000 K

ELECTRICAL

excl. power supply

9 V

LED Inset 4 W

350 mA

Class 3

Safety distance 0.3 m

PHYSICAL

Length 80 mm

Width 30 mm

Height 80 mm

0.27 kg

CUTOUT

Length 66 mm

Width 66 mm

Min. ceiling thickness 12 mm

Recessed depth 40 mm


Project

Type


Notes

Quantity

Date



Square wall recessed luminaire made from aluminium; surface Signal White; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP20; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ
LIGHTING

RETO 0.8

345161W5

MOUNTING

Concrete Housing

L · W · H (MM)

69 · 69 · 61

ORDERCODE

9 0 0 1 2 0 4 6

Recessed Housing incl. plasterkit

L · W · H (MM)

110 · 110 · 64

ORDERCODE

9 0 0 1 2 0 4 7

ELECTRICAL

Driver

TYPE

6W | 350mA | 3-22V

L · W · H (MM)

68 · 35 · 21

ORDERCODE

9 0 2 1 3 2 0 2