



WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 0.8

745162A5

GENERAL

Wall

Recessed

Anthracite Grey

Below IP65

Exterior

80 lm

LED

3000 K

ELECTRICAL

excl. power supply

24 V

LED Inset 3 W

Class 3

Safety distance 0.3 m

PHYSICAL

Length 80 mm

Width 30 mm

Height 80 mm

0.27 kg

CUTOUT

Length 66 mm

Width 66 mm

Min. ceiling thickness 12 mm

Recessed depth 40 mm

Project

Type


Notes

Quantity

Date



Square wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP65; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 0.8

745162A5

MOUNTING

Concrete Housing

L · W · H (MM)

69 · 69 · 61

ORDERCODE

9 0 0 1 2 0 4 6

Recessed Housing incl. plasterkit

L · W · H (MM)

110 · 110 · 64

ORDERCODE

9 0 0 1 2 0 4 7

ELECTRICAL

Driver

TYPE

L · W · H (MM)

ORDERCODE

35W | 24V | IP67

175 · 31 · 42,5

9 0 2 1 2 8 0 2

100W | 24V | IP67

178 · 68 · 39

9 0 2 1 2 9 0 3