



WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 1.3

745362A5

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Recessed
Anthracite Grey
Below IP65
Exterior
160 lm

LED

3000 K

ELECTRICAL

excl. power supply
24 V
LED Inset 5 W
Class 3
Safety distance 0.3 m

PHYSICAL


Length 130 mm
Width 30 mm
Height 130 mm
0.43 kg

CUTOUT

Length 115 mm
Width 117 mm
Min. ceiling thickness 12 mm
Recessed depth 40 mm



Square wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP65; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 1.3

745362A5

MOUNTING

Concrete Housing

TYPE	L · W · H (MM)	ORDERCODE
ORIS L3	120-55-120	9 0 0 1 2 0 4 0

Recessed Housing incl. plasterkit

TYPE	L · W · H (MM)	ORDERCODE
ORIS L3	160-68-160	9 0 0 1 2 0 4 1

ELECTRICAL

Driver

TYPE	L · W · H (MM)	ORDERCODE
35W 24V IP67	175-31-42,5	9 0 2 1 2 8 0 2
100W 24V IP67	178-68-39	9 0 2 1 2 9 0 3