

XAL TASK wall

059-2032038Z

PROJECT

TYPE

NOTES

QUANTITY

DATE

GENERAL

Wall
Surface
black
IP20
indirect 3530 lm
direct 1850 lm
total 5380 lm
RAL9005^a

LED

3000 K
CRI ≥ 90
R_g: 96, R_f: 90, R₁₋₁₅: 90
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
MR 0.61
MDER 0.56

OPTICAL

Microprismatic
UGR < 16

PHYSICAL

2.7 kg

ELECTRICAL

DALI-2
46 W
117 lm/W
1 DALI Addr.
PC1 220-240V

^a RAL Palette colors may deviate slightly due to production conditions.



Rectangular luminaire housing with rounded edges in aluminium; extremely flat design (only 15mm); modern shape in elegant design for discerning requirements; surface black powder coated; suitable for wall mounting; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special, inclined PCBs for asymmetric radiation characteristic; optimum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 16; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; light source not replaceable; control gear replaceable by an authorized professional;

Light Distribution

