

ELIOS ZK.K4.E120.XY

Typ: závěsné svítidlo








Stínítko: akrylátové sklo

Kovové části: hliník lakovaný – RAL 9016 (.41), RAL 3004 (.42), RAL 7023 (.43), RAL 5000 (.44) nebo RAL 9005 (.45)

Závěs: transparentní kabel

Barva: RAL9016 (.41); RAL3004 (.42); RAL7023 (.43); RAL5000 (.44); RAL9005 (.45)



W	K	Světelný tok modulu lm	Světelný tok svítidla lm	A	B	C								
5,6	4000	956	770	120	135	1500	L	–	–	–	P*	Q*	R*	1100

Lucis ZK.K4.E120.X ELIOS LED / LDC (Polar)

Napětí: 230V

IK kód: IK06

Předřadník: Driver

CRI: >80

Životnost LED: L80/F10 50000 hodin

Watt: 5,6 W

Teplota chromatičnosti: 4000 K

Světelný tok modulu: 956 lm

Světelný tok svítidla: 770 lm

A: 120 mm

B: 135 mm

C: 1500 mm

Dali 1: Dostupné

Dali 2: Nedostupné

Koridor funkce: Nedostupné

Pohybový senzor: Nedostupné

Nouzový modul: Dostupné na poptávku

Bluetooth ovládání: Dostupné na poptávku

Track systém: Dostupné na poptávku

Hmotnost: 1100 g

Luminaire: Lucis ZK.K4.E120.X ELIOS LED
Lamps: 1 x LED 103/73-840 G4

