



BETO circle 1600 suspended DIRECT

074-7404537R

PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____

GENERAL

Ceiling _____
Suspended _____
white _____
2920 lm/m _____
IP20 _____
13400 lm _____
RAL9010 ^a _____

LED

3000 K _____
CRI ≥ 80 _____
L90 / 50000 h _____
initial MacAdam ≤ 3 SDCM _____
MR 0.54 _____
MDER 0.49 _____

OPTICAL

Reflector _____
Symmetric _____
UGR < 19 _____
≥65° <1500 cd/m² _____

PHYSICAL

diameter 1569 mm _____
height 42 mm _____

ELECTRICAL

DALI-2 _____
98 W _____
137 lm/W _____
1 DALI Addr. _____
PC1 220-240V _____
21 W/m _____

^a RAL Palette colors may deviate slightly due to production conditions.



stiker 1.pdf
stiker 2.pdf

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; extremely slim design (only 42 x 42 mm); surface white powder coated; suspended luminaire with 1500mm cable suspension (canopy central); with integrated tool-less suspension height adjustment; incl. transparent feed; extruded profile for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high-quality, chromed reflector with faceted design; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection IP20; PC1 220-240V; internal wiring in light halogen free; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light Distribution

