



BETO circle 800 suspended DIRECT

074-7403537R

PROJECT

TYPE

NOTES

QUANTITY

DATE

GENERAL

Ceiling

Suspended

white

2910 lm/m

IP20

6720 lm

RAL9010 ^a

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

OPTICAL

Reflector

Symmetric

UGR < 19

≥65° <1500 cd/m²

PHYSICAL

diameter 807 mm

height 42 mm

ELECTRICAL

DALI-2

52 W

129 lm/W

1 DALI Addr.

PC1 220-240V

23 W/m

^a RAL Palette colors may deviate slightly due to production conditions.

3164582ProductId.png



stiker1.pdf

stiker2.pdf

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; extremely slim design (only 42 x 42 mm); surface white powder coated; suspended luminaire with 1500mm cable suspension (canopy central); with integrated tool-less suspension height adjustment; incl. transparent feed; extruded profile for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high-quality, chromed reflector with faceted design; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection IP20; PC1 220-240V; internal wiring in light halogen free; incl. DALI-2 converter; converter included in canopy; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light Distribution

