



WEVER & DUCRÉ
LIGHTING

BOX WALL 2.0 LED

331148B4

GENERAL

Wall
Surface
Jet Black
IP20
Interior
Indirect 175 lm
Direct 175 lm
Total 350 lm
9005^a

LED

3000 K
CRI 80
L70 / 50000 h
3-step binning

PHYSICAL

Length 100 mm
Width 100 mm
Height 100 mm
0.67 kg

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 11 W
PC1
0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project _____

Type _____


Notes _____

Quantity _____

Date _____



LIGHT DISTRIBUTION





BOX WALL 2.0 LED

331148B4

Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.93	0.87	0.82	0.76	0.71
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.