

CARD

0.2

750261I4

GENERAL

Floor
Recessed
Inox
IP67
IK07
Exterior
71 lm

LED

3000 K
CRI 80
L70 / 50000 h

OPTICAL

Beam angle 16°

PHYSICAL

Length 25 mm
Width 25 mm
Height 45 mm
0.06 kg

ELECTRICAL

excl. power supply
9 V
Total connected power 1.3 W
350 mA
PC3
Safety distance 0.3 m

CUTOUT

Diameter 22-24 mm
Recessed depth 60 mm



Project _____

Type _____


Notes _____

Quantity _____

Date _____



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

CARD 0.2

750261I4

CONE DIAGRAM

350mA 16°

h (m)	E0° (lx)	ø (m)
1	588	0.29
2	147	0.57
3	65	0.86
4	36	1.14
5	23	1.43

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.95	0.9	0.86	0.82	0.78
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

POWER SUPPLIES

Power Supply 350mA

TYPE	L · W · H (MM)	ORDERCODE
3W IP66 3-15V	52·30·23	9 0 2 1 3 1 0 1