


DESCO

341-r2419160


DESCO M SD SURFACE MOUNTED CEILING LUMINAIRE made of aluminium, black, similar to RAL 9005, satined PMMA opal diffuser beam 115°, light output direct, with converter, max. 500mA, dimmability: not dimmable, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	15
Bulb type	LED
Luminous flux [lm]	850/935/940
Current sec. [mA]	500
Colour temp. [K]	2700K/3000K/4000K
CRI	>90
Optics	PMMA opal diffuser
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	115°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Height [mm]	50
Diameter [mm]	240
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	0,61
Colour lamp	black
RAL	9005
EAN-Number	9010506451450
Lifetime [h]	L80 B10 20 000
Energy efficiency cl.	E
No. of luminaires B16A	22



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.