



WEVER & DUCRÉ
LIGHTING

DINOR 3.0

2553890K9

GENERAL

Ceiling

Suspended

Jet Black + Gold

IP20

Interior

510 lm

9005 ^a

LED

1800 K - 2850 K

3-step binning

OPTICAL

High Performance Opal

PHYSICAL

Diameter 760 mm

Height 235 mm

2.3 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 11 W

46 lm/W

PC2

0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type

Notes

Quantity

Date



Project

Type

Notes

Quantity

Date

Maintenance Factors


Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

SUSPENSION OPTIONS

Invisible Ceiling Suspension System

TYPE	L · W · H (MM)	ORDERCODE
Plasterkit	156 · 60 · 26	9 0 0 1 5 1 9 5



Single Suspension

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
Ceiling Base round	Signal Black	Ø84 · 29	9 0 0 5 2 0 2 1
Ceiling Base round	Pure White	Ø84 · 29	9 0 0 5 2 0 2 2
Ceiling Base semi recessed	Pure White	Ø84 · 72	9 0 0 5 2 0 2 6
Ceiling Base semi recessed	Signal Black	Ø84 · 72	9 0 0 5 2 0 2 7

