



WEVER & DUCRÉ  
LIGHTING

# EDGE 4.0

721274D4

## GENERAL

Floor

Surface

Dark Grey Texture

IP65

Exterior

475 lm

## LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

## PHYSICAL

Length 130 mm

Width 130 mm

Height 400 mm

3.3 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8 W

PC1

Safety distance 0.3 m

Project

Type

Notes

Quantity


Date



IP65    0,3 m



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# EDGE 4.0

721274D4

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.88	0.83	0.77	0.72
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.