

EDGE 2.0

721174D4

GENERAL

Floor
Surface
Dark Grey Texture
IP65
Exterior
475 lm

LED

3000 K
CRI 80
L70 / 50000 h
3-step binning

PHYSICAL

Length 130 mm
Width 130 mm
Height 200 mm
2.4 kg

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 8 W
PC1
Safety distance 0.3 m

Project _____

Type _____

Notes _____

Quantity _____


Date _____



IP65    <0,3>D



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

EDGE 2.0

721174D4

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.88	0.83	0.77	0.72
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.