

ILANE 1.0

9003S213 911991B2

GENERAL

Ceiling , Surface
Black Matt
Black
RAL 9005 ^a
356 lm/m
IP20
Interior
Output: 710 lm
CIE flux code: 45 77 94 99 100

LED

2700 K
CRI ≥ 90

OPTICAL

Opal ,

ELECTRICAL

24 V
Total connected power 20.4 W
Class 3
10 W/m

PHYSICAL

Length 2000 mm
Width 17 mm
Height 8 mm
0.11 kg
0.06 kg/m

^a Color may deviate slightly due to production conditions.



Project _____

Type _____


Notes _____

Quantity _____


Date _____



Ceiling surface luminaire made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; degree of protection IP20; PC3; driver not included; opal diffuser not included;



LIGHT DISTRIBUTION



ILANE

1.0

9003S213 911991B2

ELECTRICAL

Mini Connector

TYPE	L · W · H (MM)	ORDERCODE
strip to wire ILANE	120·10·3	9 0 0 1 4 2 6 8
strip to strip wired ILANE	120·10·3	9 0 0 1 4 2 6 9
strip to strip - continuous ILANE	16·10·3	9 0 0 1 4 2 7 2

Driver

TYPE	L · W · H (MM)	ORDERCODE
25W 24V phase-cut dim	128·52·30	9 0 2 2 2 7 0 1

OPTICAL

Double side adhesive tape

TYPE	LENGTH (MM)	ORDERCODE
3.0m ILANE	3000	9 0 0 1 9 1 9 9

Black Diffuser Cover

TYPE	L · W · H (MM)	ORDERCODE
2.0m ILANE	2000·15·3	9 1 1 9 0 2 B 1
2.0m ILANE	2000·15·3	9 1 1 9 1 2 B 1

MOUNTING

Surface Housing 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·17·8	9 1 1 9 9 1 B 2
2.0m ILANE	White	2000·17·8	9 1 1 9 9 1 W 2

Surface Housing 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·16·13	9 1 1 9 9 2 B 2
2.0m ILANE	White	2000·16·13	9 1 1 9 9 2 W 2

Surface Housing 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·20·20	9 1 1 9 9 3 B 2
2.0m ILANE	White	2000·20·20	9 1 1 9 9 3 W 2

Recessed Housing 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·25·13	9 1 1 9 9 4 B 2
2.0m ILANE	White	2000·25·13	9 1 1 9 9 4 W 2