

GENERAL

Ceiling , Surface

White LED Stripe

882 lm/m

IP20

Interior

Output: 1760 lm

CIE flux code: 40 69 88 99 100

LED

2700 K

CRI ≥ 90

OPTICAL

Opal ,

ELECTRICAL

24 V

Total connected power 20.0 W

Class 3

10 W/m

PHYSICAL



Length 2000 mm

Width 8 mm


Height 2 mm

0.03 kg


0.01 kg/m



Ceiling recessed or surface luminaire made from die-cast aluminium; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; degree of protection IP20; PC3; mounting housing not included; driver not included; opal diffuser not included;



LIGHT DISTRIBUTION



ILANE

9003S213

ELECTRICAL

Mini Connector

TYPE	L · W · H (MM)	ORDERCODE
strip to wire ILANE	120·10·3	9 0 0 1 4 2 6 8
strip to strip wired ILANE	120·10·3	9 0 0 1 4 2 6 9
strip to strip - continuous ILANE	16·10·3	9 0 0 1 4 2 7 2

Driver

TYPE	L · W · H (MM)	ORDERCODE
25W 24V phase-cut dim	128·52·30	9 0 2 2 2 7 0 1

MOUNTING

Surface Housing 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·17·8	9 1 1 9 9 1 B 2
2.0m ILANE	White	2000·17·8	9 1 1 9 9 1 W 2

Surface Housing 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·16·13	9 1 1 9 9 2 B 2
2.0m ILANE	White	2000·16·13	9 1 1 9 9 2 W 2

Surface Housing 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·20·20	9 1 1 9 9 3 B 2
2.0m ILANE	White	2000·20·20	9 1 1 9 9 3 W 2

Recessed Housing 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m ILANE	Black	2000·25·13	9 1 1 9 9 4 B 2
2.0m ILANE	White	2000·25·13	9 1 1 9 9 4 W 2

OPTICAL

Double side adhesive tape

TYPE	LENGTH (MM)	ORDERCODE
3.0m ILANE	3000	9 0 0 1 9 1 9 9

Black Diffuser Cover

TYPE	L · W · H (MM)	ORDERCODE
2.0m ILANE	2000·15·3	9 1 1 9 0 2 B 1
2.0m ILANE	2000·15·3	9 1 1 9 1 2 B 1