

# ILANE 4.0

9003S213 911994B2

## GENERAL

Ceiling , Surface  
Black Matt  
Black  
RAL 9005 <sup>a</sup>  
263 lm/m  
IP20  
Interior  
Output: 525 lm  
CIE flux code: 45 77 94 99 100

## LED

2700 K  
CRI ≥ 90

## OPTICAL

Opal ,

## ELECTRICAL

24 V  
Total connected power 20.6 W  
Class 3  
10 W/m

## PHYSICAL


Length 2000 mm  
Width 25 mm  
Height 13 mm  
0.24 kg  
0.12 kg/m

## CUTOUT

Length 2000 mm  
Width 21 mm  
Min. ceiling thickness 20 mm

<sup>a</sup> Color may deviate slightly due to production conditions.

## LIGHT DISTRIBUTION



[9003S213', '911994B2'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever &amp; Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · [www.weverducre.com](http://www.weverducre.com)



Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_



Ceiling recessed luminaire made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; 24 V; degree of protection IP20; PC3; driver not included; opal diffuser not included;



ILANE

4.0

9003S213 911994B2

ELECTRICAL

Mini Connector

TYPE	L · W · H (MM)	ORDERCODE
strip to wire   ILANE	120·10·3	9 0 0 1 4 2 6 8
strip to strip wired   ILANE	120·10·3	9 0 0 1 4 2 6 9
strip to strip - continuous   ILANE	16·10·3	9 0 0 1 4 2 7 2

Driver

TYPE	L · W · H (MM)	ORDERCODE
25W   24V   phase-cut dim	128·52·30	9 0 2 2 2 7 0 1

OPTICAL

Double side adhesive tape

TYPE	LENGTH (MM)	ORDERCODE
3.0m   ILANE	3000	9 0 0 1 9 1 9 9

Black Diffuser Cover

TYPE	L · W · H (MM)	ORDERCODE
2.0m   ILANE	2000·15·3	9 1 1 9 0 2 B 1
2.0m   ILANE	2000·15·3	9 1 1 9 1 2 B 1

MOUNTING

Surface Housing 1.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m   ILANE	Black	2000·17·8	9 1 1 9 9 1 B 2
2.0m   ILANE	White	2000·17·8	9 1 1 9 9 1 W 2

Surface Housing 2.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m   ILANE	Black	2000·16·13	9 1 1 9 9 2 B 2
2.0m   ILANE	White	2000·16·13	9 1 1 9 9 2 W 2

Surface Housing 3.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m   ILANE	Black	2000·20·20	9 1 1 9 9 3 B 2
2.0m   ILANE	White	2000·20·20	9 1 1 9 9 3 W 2

Recessed Housing 4.0

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
2.0m   ILANE	Black	2000·25·13	9 1 1 9 9 4 B 2
2.0m   ILANE	White	2000·25·13	9 1 1 9 9 4 W 2