



## Description

Nature and its life-giving beauty and strength serve as the model for a unique lighting concept called IVY. Just as the plant grows and climbs up the walls of a house, creating multiple images.

## Tech. description

The main body of the light comprises a dural frame and glass shades fitted with G4 sockets. The frame is connected to the power cable by means of an integrated Brokis connector. The power cable is hung from the ceiling canopy, which also houses the electronics.




Colours options: [https://brokis.sharepoint.com/:b:/s/brokis\\_sp/Ec2vgTGYUbtEndVZPRpqdZcBFcg9hmJrYa88UIPN6jSvdw](https://brokis.sharepoint.com/:b:/s/brokis_sp/Ec2vgTGYUbtEndVZPRpqdZcBFcg9hmJrYa88UIPN6jSvdw)

## CONSTRUCTION SPECIFICATION

|                               |              |
|-------------------------------|--------------|
| <b>Weight:</b>                | 2.5 kg       |
| <b>Construction material:</b> | glass, metal |
| <b>Cord length [mm]:</b>      | 2,000 mm     |
| <b>Mounting:</b>              | Ceiling      |
| <b>Environment:</b>           | Indoor       |

## DIMENSIONS [mm]



## ELECTRICAL SPECIFICATION

|                           |                                   |
|---------------------------|-----------------------------------|
| <b>Input voltage [V]:</b> | 100 - 240 V                       |
| <b>Frequency [Hz]:</b>    | 50-60 Hz                          |
| <b>Max. power [W]:</b>    | 4 x 2 W LED                       |
| <b>Coverage IP:</b>       | 20                                |
| <b>Socket:</b>            | G4, 12V                           |
| <b>Light source:</b>      | -                                 |
| <b>Energy class:</b>      | A+ to B depending on light source |

## CERTIFICATIONS





### CM6200

|                              |              |
|------------------------------|--------------|
| <b>Socket</b>                | G4           |
| <b>Type</b>                  | LED          |
| <b>Lamp wattage [W]</b>      | 1.2 W        |
| <b>Input voltage [V]</b>     | 12 VDC       |
| <b>Energy class</b>          | A+           |
| <b>Flux [lm]</b>             | 91 lm        |
| <b>Light colour [K]</b>      | 2700 K       |
| <b>CRI</b>                   | 90+          |
| <b>Lifespan [h]</b>          | 20000h       |
| <b>Dimmable</b>              | yes          |
| <b>Dimensions h x w [mm]</b> | 10 x 28,4 mm |



# DATASHEET

## RECOMENDED CANOPY




Download

### CEILING CANOPY


|                       |             |
|-----------------------|-------------|
| Dimensions O x w [mm] | 80 x 150 mm |
| Weight [kg]           | 0.85 kg     |
| Material              | metal       |



### Drawing



### Canopy bracket



# DATASHEET


## RECOMENDED CANOPY




Download

### CEILING CANOPY

|                       |                |
|-----------------------|----------------|
| Dimensions O x w [mm] | 101,5 x 220 mm |
| Weight [kg]           | 1.6 kg         |
| Material              | metal          |



### Drawing



### Canopy bracket

