



WEVER & DUCRÉ
LIGHTING

LEENS 1.0

311174B5

GENERAL

Wall

Surface

Jet Black

IP20

Interior

300 lm

9005^a

LED

3000 K

CRI 90

L90 / 50000 h

3-step binning

OPTICAL

Wide Flood

Beam angle 91°

PHYSICAL

Length 130 mm

Width 130 mm

Height 30 mm

1.1 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 3.7 W

PC1

0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type


Notes

Quantity

Date



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

LEENS 1.0

311174B5

CONE DIAGRAM

wide flood 91°

h (m)	E0° (lx)	ø (m)
1	163	2.05
2	40	4.10
3	18	6.16
4	10	8.21
5	6	10.26

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.