

# LINUS 3.0

726373A4

## GENERAL

Floor  
Surface  
Anthracite Grey  
IP65  
Exterior  
230 lm  
7016 <sup>a</sup>

## LED

3000 K  
CRI 80  
L70 / 50000 h  
3-step binning

## PHYSICAL

Length 70 mm  
Width 70 mm  
Height 150 mm  
0.52 kg

## ELECTRICAL

220 - 240 V  
Total connected power 7.1 W  
PC1  
Safety distance 0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.


Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_

Quantity \_\_\_\_\_


Date \_\_\_\_\_



IP65    0,3°



## LIGHT DISTRIBUTION



# LINUS 3.0

726373A4

## BASE

### BASE 150

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
LINUS	Anthracite Grey	110-110-150	9 1 0 0 2 4 A 0
LINUS	Dark Grey Texture	110-110-150	9 1 0 0 2 4 D 0
LINUS	Brown Texture	110-110-150	9 1 0 0 2 4 Y 0

### BASE 350

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
LINUS	Anthracite Grey	110-110-350	9 1 0 0 2 6 A 0
LINUS	Dark Grey Texture	110-110-350	9 1 0 0 2 6 D 0
LINUS	Brown Texture	110-110-350	9 1 0 0 2 6 Y 0

### BASE 550

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
LINUS	Anthracite Grey	110-110-550	9 1 0 0 2 8 A 0
LINUS	Dark Grey Texture	110-110-550	9 1 0 0 2 8 D 0
LINUS	Black Texture	110-110-550	9 1 0 0 2 8 Y 0

## GROUND SPIKE

### Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
LINUS	112-112-357	9 0 0 1 3 1 0 3

### Ground Fixation

TYPE	L · W · H (MM)	ORDERCODE
LINUS	112-112-359	9 0 0 1 3 3 0 2