



WEVER & DUCRÉ
LIGHTING

LINUS 2.0

726273A4

GENERAL

Floor

Surface

Anthracite Grey

IP65

Exterior

235 lm

7016 ^a

LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

PHYSICAL

Length 70 mm

Width 70 mm

Height 250 mm

0.99 kg

ELECTRICAL

220 - 240 V

Total connected power 7.2 W

PC2

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

Project

Type


Notes

Quantity


Date



IP65    0,3°



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

LINUS 2.0

726273A4

BASE

BASE 150

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
LINUS	Anthracite Grey	110-110-150	9 1 0 0 2 4 A 0
LINUS	Dark Grey Texture	110-110-150	9 1 0 0 2 4 D 0
LINUS	Brown Texture	110-110-150	9 1 0 0 2 4 Y 0

BASE 350

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
LINUS	Anthracite Grey	110-110-350	9 1 0 0 2 6 A 0
LINUS	Dark Grey Texture	110-110-350	9 1 0 0 2 6 D 0
LINUS	Brown Texture	110-110-350	9 1 0 0 2 6 Y 0

BASE 550

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
LINUS	Anthracite Grey	110-110-550	9 1 0 0 2 8 A 0
LINUS	Dark Grey Texture	110-110-550	9 1 0 0 2 8 D 0
LINUS	Black Texture	110-110-550	9 1 0 0 2 8 Y 0

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
LINUS	112-112-357	9 0 0 1 3 1 0 3

Ground Fixation

TYPE	L · W · H (MM)	ORDERCODE
LINUS	112-112-359	9 0 0 1 3 3 0 2