



WEVER & DUCRÉ
LIGHTING

MAP 0.9

751264I4

Project

Type

Notes

Quantity

Date

GENERAL

Floor

Recessed

Inox

IP67

IK08

Exterior

475 lm

LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

OPTICAL

Flood

Flood

Beam angle 44°

PHYSICAL

Diameter 85 mm

Height 120 mm

0.7 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.7 W

PC2

Safety distance 0.3 m


CUTOUT

Diameter 78 mm


Recessed depth 135 mm



IP67    44°



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

MAP 0.9

751264I4

CONE DIAGRAM

flood 44°

h (m)	EO° (lx)	ø (m)
1	736	0.81
2	184	1.62
3	81	2.43
4	46	3.24
5	29	4.05

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.88	0.83	0.77	0.72
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Recessed Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 0.9 CHART 0.9	ø132 · 125	9 0 0 1 2 2 0 2