

MIRBA

3.0

328384W3

GENERAL

| | |
|--|-------|
| Wall | |
| Surface | |
| Opal PMMA | |
| IP44 | |
| Interior | |
| 610 ^a to 1050 ^b lm | |

LED

| | |
|----------------|-------|
| 2700 K | |
| 3-step binning | |

OPTICAL

| | |
|------|-------|
| Opal | |
|------|-------|

PHYSICAL

| | |
|---------------|-------|
| Length 909 mm | |
| Width 60 mm | |
| Height 40 mm | |
| 0.69 kg | |

ELECTRICAL


| | |
|--|-------|
| incl. PS output selector phase-cut | |
| dim | |
| 220 - 240 V | |
| Total connected power 12 ^a to 18 ^b W | |
| PC1 | |
| Safety distance 0.3 m | |
| 13 ^a to 20 ^b W/m | |

^a Low Output

^b High Output



IP44



MIRBA

3.0

328384W3

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.94 | 0.89 | 0.83 | 0.78 | 0.73 |
| LSF | 1 | 1 | 1 | 1 | 1 |

MF $LMF \times RSMF \times LLMF \times LSF$ RSMFa Room Surface Maintenance Factor

MF Maintenance Factor LLMF Lamp Lumens Maintenance Factor

LMFa Luminaire Maintenance Factor LSF Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.