



WEVER & DUCRÉ
LIGHTING

PACE 4.0

723174W5

Project

Type

Notes

Quantity

Date

GENERAL

Floor

Surface

Signal White

IP65

Exterior

420 lm

9003^a

LED

3000 K

CRI 90

L95 / 50000 h

3-step binning

OPTICAL

Wide Flood

PHYSICAL

Length 130 mm

Width 60 mm

Height 400 mm

1 kg

ELECTRICAL

incl. PS | phase-cut dim

220 - 240 V


Total connected power 8 W

PC1


Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

IP65   



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

PACE 4.0

723174W5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$		RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE PACE	58 · 70 · 356	9 0 0 1 3 1 0 2