



WEVER & DUCRÉ
LIGHTING

PACE 8.0

723374W5

Project

Type

Notes

Quantity

Date

GENERAL

Floor
Surface
Signal White
IP65
Exterior
420 lm
9003^a

LED

3000 K
CRI 90
L95 / 50000 h
3-step binning

OPTICAL

Wide Flood

PHYSICAL

Length 130 mm
Width 60 mm
Height 800 mm
1.6 kg


ELECTRICAL

incl. PS | phase-cut dim
220 - 240 V
Total connected power 8 W
PC1
Safety distance 0.3 m


^a RAL Palette colors may deviate slightly due to production conditions.



IP65 $\leq 0,3 \text{ m}$



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

PACE 8.0

723374W5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE PACE	58-70-356	9 0 0 1 3 1 0 2