



WEVER & DUCRÉ
LIGHTING

PERLEZ IP44 3.0

192381W5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Semi-Recessed

White Opal Glass

Front IP44

Back IP20

Interior

Output: 650^a, 870^b lm

LED

3000 K

3 SDCM

OPTICAL

Opal,

ELECTRICAL

excl. driver

18 V

LED Inset 6.0^a to 9.0^b W

Class 3

350 to 500 mA

PHYSICAL

Diameter 200 mm

Height 139 mm

0.64 kg

wire springs

CUTOUT

Diameter 50-55 mm



Min. ceiling thickness 4 mm

Max. ceiling thickness 25 mm

Recessed depth 68 mm

^a 350mA

^b 500mA



PERLEZ
IP44 3.0

192381W5

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
6W 350mA	67 · 39 · 22	8.6-18V	9 0 2 1 3 3 0 3
10W 500mA 11-20V	100 · 43 · 23	11-20V	9 0 2 1 4 4 0 5
10W 500mA	65 · 39 · 20	13-20V	9 0 2 1 4 4 0 6
7W 350mA	69 · 34 · 22	12-21V	9 0 2 2 3 3 0 1
10W 350mA 1-10V dim	101.5 · 51 · 29.5	14-28V	9 0 2 2 3 4 0 1
10W 350mA phase-cut dim	102 · 38 · 21	12-28V	9 0 2 2 3 4 0 2