



WEVER & DUCRÉ
LIGHTING

PLANO ADJUST fort 1.0 LED

118961B5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Jet Black

IP20

Interior

2490 lm

9005^a

LED

3000 K

CRI 90

L80 / 50000 h

3-step binning

OPTICAL

Beam angle 41°

PHYSICAL

Length 120 mm

Width 120 mm


Height 120 mm

0.38 kg

Tilt min 30°

Tilt max 30°

Rotation 355°



ELECTRICAL

excl. power supply


36 V

Total connected power 29 W

700 mA

PC3

Safety distance 0.3 m



CUTOUT

Length 111 mm

Width 111 mm


Min. ceiling thickness 4 mm

Max. ceiling thickness 25 mm

Recessed depth 130 mm

^a RAL Palette colors may deviate slightly due to production conditions.

LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

PLANO ADJUST fort 1.0 LED

118961B5

CONE DIAGRAM

41°

h (m)	E0° (lx)	ø (m)
1	4830	0.74
2	1210	1.48
3	536	2.22
4	302	2.96
5	193	3.71

ELECTRICAL

Power Supply 700mA

TYPE	L · W · H (MM)	ORDERCODE
30W dim 10-100%	137.6·44·30	9 0 2 2 5 7 0 2
30W 6-43V DALI 0-100%	103·67·22	9 0 2 4 5 7 0 2