

REED 2.0

770282A3

GENERAL

Floor , Surface
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
Output: 450 lm

LED

2700 K
3 SDCM

OPTICAL

Opal ,

ELECTRICAL

excl. driver
24 V
LED Inset 5.0 W
Class 3

PHYSICAL

Diameter 20 mm
Height 900 mm
0.3 kg

^a Color may deviate slightly due to production conditions.


Project _____

Type _____


Notes _____

Quantity _____

Date _____



IP65  



REED
2.0

770282A3

Driver

Plug & Play Driver

TYPE	L · W · H (MM)	ORDERCODE
24W IP67	118·35·26	9 0 0 1 8 0 1 4
60W IP67	162,5·43·32	9 0 0 1 8 0 1 5

Optional

Plug & Play T-Connector

L · W · H (MM)	ORDERCODE
48·24·15	9 0 0 1 4 5 0 1

Plug & Play Extension Cable

TYPE	LENGTH (MM)	ORDERCODE
2,5 m IP67	2500	9 0 0 1 4 5 0 2
5 m IP67	5000	9 0 0 1 4 5 0 3

Plug & Play Straight Connector

TYPE	ORDERCODE
	9 0 0 1 4 5 0 4