



WEVER & DUCRÉ
LIGHTING

ROB 1.6

701184W3

GENERAL

Ceiling

Surface

Signal White

IP44

Interior

872 lm

9003 ^a

LED

2700 K

CRI 90

L80 / 50000 h

3-step binning

PHYSICAL

Diameter 160 mm

Height 60 mm

0.7 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 13 W

67 lm/W

PC1

0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type


Notes

Quantity


Date



IP44  



LIGHT DISTRIBUTION



ROB

1.6

701184W3

Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.93	0.91	0.89
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical

DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18·48·46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55·17·90	9 0 0 1 9 0 1 8