



WEVER & DUCRÉ
LIGHTING

ROOMOR WALL 4.0

339620BB1

GENERAL

Wall

Surface

Jet Black

Mounting Jet Black

Shade Jet Black

IP20

Interior

320 lm

9005^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 15 W

OPTICAL

Shade 1.0

PHYSICAL

Diameter 205 mm

Height 1220 mm

1.3 kg

cabl base round

Tilt min 45°

Tilt max 45°

Rotation 30°

ELECTRICAL

100 - 240 V

Total connected power 8.6 W

PC1

^a RAL Palette colors may deviate slightly due to production conditions.



Project

Type


Notes

Quantity

Date



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

ROOMOR WALL 4.0

339620BB1

SHADE 2.0

Shade 2.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	ø250-150	9 1 1 3 6 2 0 B 1
ROOMOR	Black Texture + Gold	ø250-150	9 1 1 3 6 2 0 K 1
ROOMOR	Felt Grey	ø250-150	9 1 1 3 6 2 F T 1
ROOMOR	Grey + White	ø250-150	9 1 1 3 6 2 G W 1
ROOMOR	Coral Red + White Texture	ø250-150	9 1 1 3 6 2 R W 1

SHADE 1.0

Shade 1.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	ø205-70	9 1 1 3 6 1 0 B 1
ROOMOR	Black Texture + Gold	ø205-70	9 1 1 3 6 1 0 K 1
ROOMOR	Felt Grey	ø205-70	9 1 1 3 6 1 F T 1
ROOMOR	Grey + White	ø205-70	9 1 1 3 6 1 G W 1
ROOMOR	Coral Red + White Texture	ø205-70	9 1 1 3 6 1 R W 1

SHADE 3.0

Shade 3.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	ø405-15	9 1 1 3 6 3 0 B 1
ROOMOR	Black Texture + Gold	ø405-150	9 1 1 3 6 3 0 K 1
ROOMOR	Felt Grey	ø405-150	9 1 1 3 6 3 F T 1
ROOMOR	Grey + White	ø405-150	9 1 1 3 6 3 G W 1
ROOMOR	Coral Red + White Texture	ø405-150	9 1 1 3 6 3 R W 1

SHADE 4.0

Shade 4.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	ø510-75	9 1 1 3 6 4 0 B 1
ROOMOR	Black Texture + Gold	ø510-75	9 1 1 3 6 4 0 K 1
ROOMOR	Felt Grey	ø510-75	9 1 1 3 6 4 F T 1
ROOMOR	Grey + White	ø510-75	9 1 1 3 6 4 G W 1
ROOMOR	Coral Red + White Texture	ø510-75	9 1 1 3 6 4 R W 1

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	ø50-58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	ø50-58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	ø50-58	9 0 1 2 2 8 W 4