



WEVER & DUCRÉ
LIGHTING

ROOMOR WALL 4.0

339620BB3

GENERAL

Wall
Surface
Jet Black
Mounting Jet Black
Shade Jet Black
IP20
Interior
320 lm
9005^a

LED

Lamp PAR16
PAR16
Socket GU10
max. 15 W

OPTICAL

Shade 3.0

PHYSICAL

Diameter 405 mm
Height 1220 mm
1.3 kg
cable base round
Tilt min 45°
Tilt max 45°
Rotation 30°

ELECTRICAL

100 - 240 V
Total connected power 8.6 W
PC1

^a RAL Palette colors may deviate slightly due to production conditions.



Project

Type


Notes

Quantity

Date



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

ROOMOR WALL 4.0

339620BB3

SHADE 2.0

Shade 2.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	Ø250-150	9 1 1 3 6 2 0 B 1
ROOMOR	Black Texture + Gold	Ø250-150	9 1 1 3 6 2 0 K 1
ROOMOR	Felt Grey	Ø250-150	9 1 1 3 6 2 F T 1
ROOMOR	Grey + White	Ø250-150	9 1 1 3 6 2 G W 1
ROOMOR	Coral Red + White Texture	Ø250-150	9 1 1 3 6 2 R W 1

SHADE 1.0

Shade 1.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	Ø205-70	9 1 1 3 6 1 0 B 1
ROOMOR	Black Texture + Gold	Ø205-70	9 1 1 3 6 1 0 K 1
ROOMOR	Felt Grey	Ø205-70	9 1 1 3 6 1 F T 1
ROOMOR	Grey + White	Ø205-70	9 1 1 3 6 1 G W 1
ROOMOR	Coral Red + White Texture	Ø205-70	9 1 1 3 6 1 R W 1

SHADE 3.0

Shade 3.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	Ø405-15	9 1 1 3 6 3 0 B 1
ROOMOR	Black Texture + Gold	Ø405-150	9 1 1 3 6 3 0 K 1
ROOMOR	Felt Grey	Ø405-150	9 1 1 3 6 3 F T 1
ROOMOR	Grey + White	Ø405-150	9 1 1 3 6 3 G W 1
ROOMOR	Coral Red + White Texture	Ø405-150	9 1 1 3 6 3 R W 1

SHADE 4.0

Shade 4.0

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ROOMOR	Jet Black	Ø510-75	9 1 1 3 6 4 0 B 1
ROOMOR	Black Texture + Gold	Ø510-75	9 1 1 3 6 4 0 K 1
ROOMOR	Felt Grey	Ø510-75	9 1 1 3 6 4 F T 1
ROOMOR	Grey + White	Ø510-75	9 1 1 3 6 4 G W 1
ROOMOR	Coral Red + White Texture	Ø510-75	9 1 1 3 6 4 R W 1

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	Ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	Ø50-58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	Ø50-58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	Ø50-58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	Ø50-58	9 0 1 2 2 8 W 4