

## SENSE 68 Round

Manufacture: NEKO LIGHTING AG

Type: SENSE Modular Downlight STR2-9272411F-WW



### General

- Indoor
- Downlight
- Recessed
- Version: round
- Housing: white
- Reflector: white
- IP 20

### LED

- 2700K
- CRI 90
- LED Output: 1100lm
- System Output: 750lm
- 50000h@L80B10
- SDCM: 3



### Optics

- Beam angle: 24°
- UGR <19

### Electric

- LED Driver: ON-OFF
- LED Power: 11W
- System Power: 13W
- 31V
- 350mA


### Dimensions

- Measurement: Ø78mm
- Cutout: Ø68mm
- Height: 98mm
- Ceiling height: 148mm
- Net Weight: 260g
- Gross Weight: 380g
- Pivot: max. 30°
- Rotation: 355°


### Description

Round recessed ceiling downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and white reflector; ON-OFF Driver; LED 11W; measurement Ø78mm; ceiling cutout of Ø68mm with a narrow mounting trim; luminaire's weight is approximately 260g; CCT 2700K with an LED Output of 1100lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; narrow beam characteristic with 24° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)


### Light distribution



### Technical drawing



Ø68mm



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.