



WEVER & DUCRÉ
LIGHTING

STIPO 4.0

737467D4

GENERAL

Floor

Surface

Dark Grey Texture

IP65

Exterior

505 lm

LED

3000 K

CRI 80

3-step binning

OPTICAL

Beam angle 39°

PHYSICAL

Diameter 52 mm

Height 120 mm

0.49 kg

Tilt min 135°

Tilt max 135°

ELECTRICAL

220 - 240 V

Total connected power 7.3 W

PC2

Safety distance 0.3 m

Project




Type

Notes

Quantity


Date



IP65    0,3 m



LIGHT DISTRIBUTION






WEVER & DUCRÉ
LIGHTING

STIPO 4.0

737467D4

CONE DIAGRAM



GROUND SPIKE

Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
STAKE 1.0 STIPO	Ø 122 · 357	9 0 0 1 3 1 0 6

POLE

POLE 200

TYPE	COLOUR	ORDERCODE
STIPO incl. Base excl. Spike	Dark Grey Texture	9 1 0 0 6 2 D 0
STIPO incl. Base excl. Spike	Brown Texture	9 1 0 0 6 2 Y 0

POLE 400

TYPE	COLOUR	ORDERCODE
STIPO incl. Base excl. Spike	Dark Grey Texture	9 1 0 0 6 4 D 0
STIPO incl. Base excl. Spike	Brown Texture	9 1 0 0 6 4 Y 0

POLE 600

TYPE	COLOUR	ORDERCODE
STIPO incl. Base excl. Spike	Dark Grey Texture	9 1 0 0 6 6 D 0
STIPO incl. Base excl. Spike	Brown Texture	9 1 0 0 6 6 Y 0

POLE 800

TYPE	COLOUR	ORDERCODE
STIPO incl. Base excl. Spike	Dark Grey Texture	9 1 0 0 6 8 D 0
STIPO incl. Base excl. Spike	Brown Texture	9 1 0 0 6 8 Y 0