



WEVER & DUCRÉ
LIGHTING

STRIPE 2.2

305351B4

GENERAL

Wall

Recessed

Jet Black

IP20

Interior

16^a to 28^b lm

9005^c

LED

3000 K

CRI 80

L90 / 50000 h

3-step binning

OPTICAL

Asymmetric Wallwasher

PHYSICAL

Length 35 mm

Width 37 mm

Height 220 mm

0.27 kg

ELECTRICAL

excl. power supply

3 V

Total connected power 1.4^a to 2.8^b W

350^a to 700^b mA

PC3

0.3 m

CUTOUT

Length 25 mm

Width 170 mm

Min. ceiling thickness 2 mm

Max. ceiling thickness 18 mm




Recessed depth 40 mm

^a 350mA

^b 700mA

^c RAL Palette colors may deviate slightly due to production conditions.

LIGHT DISTRIBUTION



Project

Type

Notes

Quantity

Date





WEVER & DUCRÉ
LIGHTING

STRIPE 2.2

305351B4

MOUNTING

Plasterkit + Recessed Housing

TYPE	L · W · H (MM)	ORDERCODE
STRIPE 2.2	100 · 50 · 280	9 0 0 1 2 0 3 8

POWER SUPPLIES

Power Supply 350mA

TYPE	L · W · H (MM)	ORDERCODE
6W 3 · 22V	64 · 35 · 21	9 0 2 1 3 2 0 2

Power Supply 700mA

TYPE	L · W · H (MM)	ORDERCODE
6W 3 · 8.4V	64 · 35 · 21	9 0 2 1 5 2 0 3