



WEVER & DUCRÉ  
LIGHTING

# TAPE 6.0

722374D5

## GENERAL

Floor

Surface

Dark Grey Texture

IP65

Exterior

Indirect 10 lm

Direct 410 lm

Total 420 lm

## LED

3000 K

CRI 90

L90 / 50000 h

3-step binning

## OPTICAL

Wide Flood

## PHYSICAL

Length 180 mm

Width 60 mm

Height 600 mm

2.6 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8 W

PC1

0.3 m

Project

Type


Notes

Quantity


Date



IP65



## LIGHT DISTRIBUTION



Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE   PACE	58-70-356	9 0 0 1 3 1 0 2