



WEVER & DUCRÉ  
LIGHTING

# TUBE WALL 2.0 LED

711264A5

## GENERAL

Wall

Surface

Anthracite Grey

IP65

Exterior

Indirect 390 lm

Direct 390 lm

Total 780 lm

## LED

3000 K

CRI 90

L95 / 50000 h

3-step binning

MR 0.59

MDER 0.54

## OPTICAL

Flood

## PHYSICAL

Diameter 80 mm

Height 152 mm

0.74 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 15.8 W

PC1

Safety distance 0.3 m

Project

Type


Notes

Quantity


Date



IP65    0.3 m



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# TUBE WALL 2.0 LED

711264A5

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.