



WEVER & DUCRÉ  
LIGHTING

# VENN 2.0

149285W2

## GENERAL

Wall

Surface

Signal White

IP20

Interior

Indirect 3030 lm

Direct 455 lm

Total 3485 lm

RAL 9003 <sup>a</sup>

## LED

2700 K

CRI 80

L80 / 50000 h

3-step binning

MR 0.47

MDER 0.42

## PHYSICAL

Length 724 mm

Width 724 mm

Height 90 mm

2.5 kg

## ELECTRICAL

DALI dim

220 - 240 V

Total connected power 46 W

PC1

Safety distance 0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.




Project

Type


Notes

Quantity

Date



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# VENN 2.0

149285W2

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.89	0.86	0.82
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## ELECTRICAL

### DIMMER

TYPE	L · W · H (MM)	ORDERCODE
DALI DIMMER FOR SWITCH	48 · 49 · 22	9 0 0 1 9 1 9 4