



WEVER & DUCRÉ
LIGHTING

VENN 2.0

149285W4

GENERAL

Wall

Surface

Signal White

IP20

Interior

Indirect 3230 lm

Direct 490 lm

Total 3720 lm

RAL 9003 ^a

LED

3000 K

CRI 80

L80 / 50000 h

3-step binning

MR 0.54

MDER 0.49

PHYSICAL

Length 724 mm

Width 724 mm

Height 90 mm

2.5 kg

ELECTRICAL

DALI dim

220 - 240 V

Total connected power 46 W

PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.



Project

Type


Notes

Quantity

Date



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

VENN 2.0

149285W4

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.89	0.86	0.82
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$		RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL

DIMMER

TYPE	L · W · H (MM)	ORDERCODE
DALI DIMMER FOR SWITCH	48 · 49 · 22	9 0 0 1 9 1 9 4