



WEVER & DUCRÉ
LIGHTING

BLAS 1.0

736187B4

GENERAL

Ceiling
Surface
Jet Black
IP65
Exterior
840 lm
9005^a

LED

3000 K
CRI 80
L70 / 50000 h
3-step binning

OPTICAL

Jut-Out

PHYSICAL

Diameter 130 mm
Height 79 mm
1 kg

ELECTRICAL


phase-cut dim
220 - 240 V
Total connected power 9.4 W
PC1
0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project
Type
Notes
Quantity
Date



IP65  



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

BLAS
1.0

736187B4

Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.89	0.83	0.78	0.73
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.