



WEVER & DUCRÉ
LIGHTING

BLAS 2.0

736287B4

GENERAL

Ceiling

Surface

Jet Black

IP65

Exterior

840 lm

9005 ^a

LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

OPTICAL

Jut-Out

PHYSICAL

Length 130 mm

Width 130 mm

Height 79 mm

1.3 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 9.4 W

PC1

0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

Project

Type


Notes

Quantity


Date



IP65  



LIGHT DISTRIBUTION



Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.89	0.83	0.78	0.73
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.