



WEVER & DUCRÉ
LIGHTING

DEEP ADJUST petit 1.0 LED

153361B5

GENERAL

Ceiling

Recessed

Jet Black

IP20

Interior

525 lm

9005^a

LED

3000 K

CRI 90

L70 / 50000 h

OPTICAL

Flood

Beam angle 34°

PHYSICAL

Diameter 79 mm

Height 60 mm

0.05 kg

Standard Springs

Tilt min 35°

Tilt max 35°

Rotation 355°

ELECTRICAL

excl. power supply

18 V

Total connected power 8.1 W

LED Inset 6.1 W

65 lm/W

350 mA

PC3

0.3 m

CUTOUT

Diameter 68-70 mm



Min. ceiling thickness 4 mm

Max. ceiling thickness 23 mm

Recessed depth 60 mm

^a RAL Palette colors may deviate slightly due to production conditions.

LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

DEEP ADJUST petit 1.0 LED

153361B5

CONE DIAGRAM

flood 34° 350mA

h (m)	E0° (lx)	ø (m)
1	1250	0.61
2	312	1.23
3	139	1.84
4	78	2.46
5	49	3.07

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL

Power Supply 350mA

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
10W 14-28V 1-10V dim	101.5 · 51 · 29.5	14 - 28V	9 0 2 2 3 4 0 1
10W 12-28V phase-cut dim	102 · 38 · 21	12 - 28V	9 0 2 2 3 4 0 2
10W 2.5-26V DALI dim 5-100%	124 · 31 · 21	2.5 - 26V	9 0 2 4 3 4 0 1
20W DALI	111 · 52 · 22		9 0 2 4 3 6 0 1