



WEVER & DUCRÉ
LIGHTING

DOCUS 2.0 LED

146464P4

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Copper

IP20

Interior

1100 lm

LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

OPTICAL

Flood

Beam angle 32°

PHYSICAL

Length 174 mm

Width 90 mm

Height 90 mm

0.92 kg

ELECTRICAL

phase-cut dim


230 V

Total connected power 16 W


69 lm/W

PC1

0.3 m



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

DOCUS 2.0 LED

146464P4

CONE DIAGRAM

flood 32°

h (m)	E0° (lx)	ø (m)
1	2670	0.58
2	668	1.15
3	297	1.73
4	167	2.31
5	107	2.88

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.88	0.83	0.77	0.72
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Single Inner Cover

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DOCUS max. 10W	Jet Black	62 · 62 · 39.5	9 1 1 0 2 1 B 1
DOCUS max. 10W	Gold	62 · 62 · 39.5	9 1 1 0 2 1 G 1
DOCUS max. 10W	Signal White	62 · 62 · 39.5	9 1 1 0 2 1 W 1