


□ DUAL CEILING



ARCHILIGHT



INSTALLATION

Suspended version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium, powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION

Direct symmetrical

EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SDC130	595x49x85	9	1340/1420
SDC250	595x49x85	12	1860/1960
SDC195	850x49x85	12	2010/2130
SDC375	850x49x85	18	2790/2940
SDC260	1135x49x85	16	2680/2840
SDC500	1135x49x85	24	3720/3920
SDC325	1415x49x85	21	3350/3550
SDC625	1415x49x85	31	4650/4900
SDC2x195	1700x49x85	26	4020/4260
SDC2x375	1700x49x85	37	5580/5880
SDC2x230	1980x49x85	29	4690/4970
SDC2x440	1980x49x85	43	6510/6860
SDC2x260	2265x49x85	33	5360/5680
SDC2x500	2265x49x85	49	7440/7840
SDC2x325	2825x49x85	41	6700/7100
SDC2x625	2825x49x85	61	9300/9800

COLOR TEMPERATURE

3000K /3K
4000K /4K


OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

ACCESSORIES



COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

