



WEVER & DUCRÉ  
LIGHTING

# MILES 3.0 ROUND

317774G5

## GENERAL

Wall  
Surface  
Gold  
IP20  
Interior  
430 lm

## LED

3000 K  
L80 / 50000 h  
3-step binning


## PHYSICAL

Length 260 mm  
Width 37 mm  
1.1 kg

## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 8 W  
PC2  
0.3 m

Project  
Type  
Notes  
Quantity  
Date





WEVER & DUCRÉ  
LIGHTING

# MILES

## 3.0 ROUND

317774G5

Project

---

Type

---

Notes

---

Quantity

---

Date

---

### Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.84	0.8
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.