



WEVER & DUCRÉ
LIGHTING

MILES 12.0

317374WN5

GENERAL

Wall
Surface
Walnut Wood
IP20
Interior
Indirect 1120 lm
Direct 1120 lm
Total 2240 lm

LED

3000 K
CRI 80
L80 / 50000 h
3-step binning


PHYSICAL

Length 1200 mm
Width 26 mm
Height 80 mm
2.6 kg


ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 38 W
PC1
0.3 m

Project
Type
Notes
Quantity
Date



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

MILES
12.0

317374WN5

Project

Type

Notes

Quantity

Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.85	0.82
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.