



WEVER & DUCRÉ  
LIGHTING

# ROBY 3.5

135384B5

## GENERAL

Ceiling

Surface

Jet Black

IP44

Interior

1800 lm

9005<sup>a</sup>

## LED

3000 K

3-step binning

## PHYSICAL

Diameter 355 mm

Height 60 mm

2.5 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 32 W

56 lm/W

PC1

0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.

Project

Type


Notes

Quantity

Date



IP44  





WEVER & DUCRÉ  
LIGHTING

# ROBY 3.5

135384B5

Project

Type

Notes

Quantity

Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.9	0.88
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Electrical

### DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18-48-46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55-17-90	9 0 0 1 9 0 1 8