



WEVER & DUCRÉ  
LIGHTING

# SELO 2.0

235289W9

## GENERAL

Ceiling

Suspended

White Porcelain

IP20

Interior

510 lm

## LED

1800 K - 2850 K

3-step binning

## OPTICAL

High Performance Opal

## PHYSICAL

Length 194 mm

Width 194 mm

Height 125 mm

0.96 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 11 W

46 lm/W

PC2

0.3 m


Project

Type

Notes

Quantity

Date





WEVER & DUCRÉ  
LIGHTING

# SELO 2.0

235289W9

Project .....

Type .....

Notes .....

Quantity .....

Date .....

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1


MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## SUSPENSION OPTIONS

### Invisible Ceiling Suspension System

TYPE	L · W · H (MM)	ORDERCODE
Plasterkit	156·60·26	9 0 0 1 5 1 9 5



### Single Suspension

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
Ceiling Base round	Signal Black	Ø84·29	9 0 0 5 2 0 2 1
Ceiling Base round	Pure White	Ø84·29	9 0 0 5 2 0 2 2
Ceiling Base   semi recessed	Pure White	Ø84·72	9 0 0 5 2 0 2 6
Ceiling Base   semi recessed	Signal Black	Ø84·72	9 0 0 5 2 0 2 7

