



WEVER & DUCRÉ
LIGHTING

SQUBE on base 2.0 LED

144464B4

GENERAL

Ceiling
Surface
Jet Black
IP20
Interior
795 lm
9005^a

LED

3000 K
CRI 80
L60 / 50000 h
3-step binning

OPTICAL

Beam angle 32°

PHYSICAL



Diameter 65 mm
Height 133 mm
0.44 kg
Tilt min 90°
Tilt max 90°

ELECTRICAL


phase-cut dim
220 - 240 V
Total connected power 12 W
PC1
0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.

Project
Type
Notes
Quantity
Date



LIGHT DISTRIBUTION





SQUBE

on base 2.0 LED

144464B4

CONE DIAGRAM

32°

h (m)	E0° (lx)	ø (m)
1	1690	0.57
2	423	1.14
3	188	1.70
4	106	2.27
5	67	2.84

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.87	0.81	0.74	0.69
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Electrical

DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18-48-46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55-17-90	9 0 0 1 9 0 1 8