



WEVER & DUCRÉ
LIGHTING

TAPE 4.0

722274D5

GENERAL

Floor
Surface
Dark Grey Texture
IP65
Exterior
Indirect 10 lm
Direct 410 lm
Total 420 lm

LED

3000 K
CRI 90
L90 / 50000 h
3-step binning

OPTICAL

Wide Flood

PHYSICAL

Length 180 mm
Width 60 mm
Height 400 mm
1.9 kg


ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 8 W
PC1
0.3 m


Project
Type
Notes
Quantity
Date



IP65



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

TAPE 4.0

722274D5

Project _____

Type _____

Notes _____

Quantity _____

Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF RSMF^a Room Surface Maintenance Factor
 MF Maintenance Factor LLMF Lamp Lumens Maintenance Factor
 LMF^a Luminaire Maintenance Factor LSF Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE PACE	58 · 70 · 356	9 0 0 1 3 1 0 2